



MATERIAL CUT LIST	Material	Unit/Length	Quantity
Metal Screw	#12 Drivall	0	1538
Metal Screw	#10 Drivall	0	80
Connector (P3)	PL9x6x0.057	0	10
Connector (P5)	PL18x9x0.057	0	20
Simpson	S/H2.5	0	20
B1	362S162-33(33)	20'-0"	10
T1	362S162-43(33)	12'-2 11/16"	10
T2	362S162-43(33)	12'-2 11/16"	10
Web #1 3	250S162-33(33)	4'-11 13/16"	20
Web #2	250S162-33(33)	3'-7 1/8"	10
Web Stiffener (ws)	250T125-33(33)	3 1/2"	20

GENERAL NOTES

- Number of fasteners noted in chart installed on each end of Web
- When connecting plates to chord or web members, fasteners must pass through the plate and member. If a joint connection has fasteners passing through the web, connector plate and chord, the fastener may be counted as part of the required number of fasteners for that joint.
- Minimum connector spacing (center to center or free edge) = 3/4"
- Truss connector type - #12 Drivall (Grabber)

Number of Trusses = 10 each
Chord Cut Type = Mitre Cut
Truss Spacing = 2'-0"
Number of Plys = 1
Weight per Truss = 63.6 lbs (per ply)



2 denotes number of fasteners @ each end of member (web or chord)
4 4 denotes number of chord-plate fasteners

Scale: 1/4" = 1'-0"



Rusk Component and Design

11357 Billings Ave
Lafayette, CO 80026
(303) 828-5747

Roof Trusses

Lafayette, Co

Truss D&E, V25.011
Date: 04-24-2015
Time: 08:06
Designer: BJR
File: C-3-20
Job Number: RoofTruss

This document contains information proprietary to Rusk Component and Design and may not be used or reproduced without prior written consent. Contents subject to change without notice.

C-3-20

Fabrication Drawing